

UNITED SR SPORTS RACING

Product Description:

Blended with high performance, field proven additive to enhance the friction-reduction properties, United SR Sports Racing 100% Fully Synthetic motor oil is formulated to cater for motoring enthusiasts who having invested considerable time and money to upgrade and/or improve their engines performance are searching for that "unique" motor oil.

United SR Sports Racing 100% Fully Synthetic motor oil recognizes the importance of a properly formulated lubricant that can withstand extreme temperature at high rpm with minimum shearing the viscosimetry of the oil.

This product is test proven by motoring enthusiasts in endurance races in Australia, race circuits in New Zealand, Malaysia, Taiwan, Macau and Indonesia.

Applications / Benefits:

- Super fluidity over wide ranges of temperature and operating conditions.
- Excellent high temperature, high shear capability.
- Superior high temperature protection.
- Additional friction modifier for added protection.

Typical Characteristics:

| Test Description | Method | |
|---------------------------------|---------------|--------|
| SAE Viscosity Grade | SAE J 300 | 10W-60 |
| Specific Gravity @ 15 °C | ASTM D 4052 | 0.8715 |
| Flash Point, °C | ASTM D 92 | 234 |
| Pour Point, °C | ASTM D 97 | -39 |
| Kinematic Viscosity, cSt @ 40°C | ASTM D 445 | 172.2 |
| cSt @ 100°C | ASTM D 445 | 24.1 |
| Viscosity Index | ASTM D 2270 | 171 |
| TBN, mgKOH/g | ASTM D 2896 | 11.0 |
| Color | ASTM D 1500 | <3.5 |
| CCS, cP | ASTM D 5293 - | ≤7000 |
| HTHS, cP | ASTM D 5481 | ≥3.7 |

Specifications, Approvals & Recommendations:

- API SP
- ACEA A3/B4





