

UNITED CLASSIC KING

Product Description

Fully synthetic passenger car motor oil formulated using high quality fully synthetic base oils and fortified with a superior additive package that meets the requirement of engines that operate for long periods of time. For high mileage vehicles, engine performance is usually not at optimum conditions, and the vehicle encounters issues such as increased oil consumption, seal leakage and drops in efficiency.

This product is blended with additives that help to restore your old engines' performance and extend your vehicle life. The crankcase booster and dispersant additives also helps to provide a cleaner engine with better wear protection and gear protection.

Applications / Benefits

- * Self-repair' seals and gaskets, prevent leakages therefore reducing oil consumption
- Specially formulated for high mileage engines with long operating hours
- * Better control of sludge and piston deposits
- * Improved oil film thickness prevents leaks through enlarged clearances

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	5W40
Density @ 15 °C	ASTM D 4052	kg/L	0.874
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	88.4
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.3
Viscosity Index	ASTM D 2270	=	169
TBN	ASTM D 2896	mgKOH/g	14.1
CCS	ASTM D 5293	cР	≤6600



Suitable for the following Uses

API SP ACEA A3/B3 ACEA A3/B4 * FIAT M2 * MERCEDES BENZ 226.5 229.3 MERCEDES BENZ MERCEDES BENZ 229.5 * PSA B71 2296 RENAULT RN 0700/0710 VOLKSWAGEN 502.00/505.00

Reference No. 4162G3SPA3B4REV0 Last revised date: 25/8/2023