

# UNITED GX PLUS

## Product Description

Passenger car motor oil (PCMO) that delivers the enhanced performance of lubricating oil technology to maximize protection for the latest gasoline fueled engines. It meets the performance level of API SP and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this oil is also formulated to improve fuel efficiency for consumers.

## Applications / Benefits

- \* Exceeds the highest U.S Lubricating oils standards for gasoline and TGDI / non TGDI engines.
- \* Improve piston cleanliness and fuel economy while maintaining sludge control.
- \* Reduce the potential for pre-ignition (LSPI) and timing chain wear.
- \* Increases emission system durability and improves fuel efficiency.

## Typical Characteristics

Test Description	Method	Unit	5W30	10W30
SAE Viscosity Grade	SAE J 300	-	5W30	10W30
Density @ 15 °C	ASTM D 4052	kg/L	0.8510	0.8590
Flash Point	ASTM D 92	°C	218	216
Pour Point	ASTM D 97	°C	-36	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	67.3	74.5
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.4	11.7
Viscosity Index	ASTM D 2270	-	165	152
TBN	ASTM D 2896	mgKOH/g	7	7
CCS	ASTM D 5293	cP	5822	5016

## Specifications, Approvals & Recommendations

- \* API SP-RC
- \* ILSAC GF-6A
- \* FORD WSS-M2C961-A1 IN SAE 5W30

Reference No.  
5178G23SPGF6REV0

Last revised date:  
13/4/2023