



UNITED MV-CHF

Product Description:

United MV-CHF is specially-formulated with selected high viscosity index synthetic base stock, PAO and chemical additives to meet various passenger car and commercial vehicle performance demands, e.g. Ford, General Motors, Mercedes Benz, Chrysler, Mitsubishi, Nissan, Kia, Hyundai, and many more. United MV-CHF is a specifically-designed fully-synthetic fluid for the commercial and passenger car industry.

United MV-CHF lubricates and transmits the required power needed for power-assisted steering with minimum sludge and deposit. It is generally compatible with most seals and hoses in power steering systems. United MV-CHF is recommended for most power steering systems and central hydraulic systems.

Applications / Benefits:

- ▣ Provides excellent friction, oxidation and thermal stability.
- ▣ Outstanding anti-wear properties.
- ▣ Improves hydrolytic stability.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.829
Flash Point, °C	ASTM D 92	180
Pour Point, °C	ASTM D 97	-51
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	19.0
cSt @ 100°C	ASTM D 445	6.36
Viscosity Index	ASTM D 2270	330
Appearance	Visual	Green



United Oil
PERFORMANCE • VALUE • RELIABILITY

Meeting the requirements of:

- Audi P/N G002000
- Audi P/N G002012
- Chrysler MS-1872
- Chrysler MS-5931, P/N 04883077
- Chrysler MS-9602, ATF+4
- Chrysler MS-10838, P/N 05142893AA
- Chrysler MS-11655
- DEXRON-IID
- DEXRON-III
- Ford M2C195-A
- GM P/N 88901975
- GM P/N 89021184
- GM 9985010, P/N 1052884
- GM 9985835, P/N 12345866 (Cold Climate)
- Hyundai/KIA PSF-3
- Hyundai/KIA PSF-4
- MB 236.3, P/N 000 989 88 03
- MB 345.0, P/N 001 989 24 03
- Mitsubshi PS Fluid
- Mitsubishi Diamond SP III
- Nissan PSF-II
- Pentosin CHF 7.1
- Pentosin CHF 11S
- Pentosin CHF 202
- Saab P/N (45) 30 09 800
- Saab P/N 30 32 380
- Subaru P/N K0209A0080
- Toyota PSF Type EH, P/N 008886-01
- VW P/N G002000
- VW P/N G002012
- Volvo P/N 1161529

Product Data Sheet