

UNITED MTB SCOOTER

Product Description:

Motorcycle operating conditions are considerably different from passenger car, resulting in increased specification complexity in the motorcycle oil market. United MTB Scooter is a tailored high-performance product to meet the unique demands of 4 stroke motorcycle. It not only lubricates critical engine components, but also provide protection for clutch assemblies and gearbox.

United MTB Scooter is formulated with the right combination and balance of component to combat undesirable potential issues such as gear pitting, clutch slip and higher levels of engine deposits. The advanced motorcycle oil is designed to deliver exceptional control from wear, corrosion and deposit formation as well as improved oxidative and thermal stability.

United MTB Scooter provides unsurpassed clutch performance and friction durability throughout the oil life, leading smoother operation and extended engine life with more consistent and enjoyable overall riding experience.

Applications / Benefits:

- I Protects engine under severe operating conditions.
- I Enhanced piston and engine cleanliness.
- I Retards harmful deposit formation on vital engine parts.
- ^I Provide clutch friction durability.
- I Prolong hardware and engine life.

Typical Characteristics:

Test Description	Method		
SAE Viscosity Grade	SAE J 300	10W-30	10W-40
Specific Gravity @ 15 °C	ASTM D 4052	0.869	0.869
Flash Point, °C	ASTM D 92	212	214
Pour Point, °C	ASTM D 97	-30	-30
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	78.1	102
cSt @ 100℃	ASTM D 445	11.8	14.9
Viscosity Index	ASTM D 2270	145	152
TBN, mgKOH/g	ASTM D 2896	7.5	7.5
Color	ASTM D 1500	2.5	2.5

Suggested for the following uses:

- API SN*
- API SL
- JASO MB

*Not applicable to SAE 10W30.