



油力特 CVTF NS-2

5800G23HIGNS2REV0

产品说书:

油力特 CVTF NS-2 是由高性能合成基础油和精心选配先进的专用添加剂调配而成，包括摩擦改善剂、清洁分散剂、抗氧化剂、粘度指数改良剂、防锈剂和消泡剂等。油力特 CVTF NS-2 是一种性能均衡的自动传输流体，特别设计用来满足现代最新技术的汽车无级变速传动 (Continuously Variable Transmissions) 的要求，它是一种以金属带作为回流调速机构的汽车无级变速传动装置，这种变速器和普通自动变速器的最大区别是它省去了复杂而又笨重的齿轮组合变速传动，而只用了两组带轮进行变速传。

由于 CVT 可以实现传动比的连续改变，从而得到传动系与发动机工况的最佳匹配，提高整车的燃油经济性和动力性，改善驾驶员的操纵方便性和乘员的乘坐舒适性，所以它是理想的汽车传动装置。

优点 / 用途:

- ▣ 提供卓越的摩擦、抗氧化和热稳定性.
- ▣ 超强的抗磨及和油膜厚度.
- ▣ 优秀低温流动性和低温启动保护
- ▣ 超长的使用寿命得益于全合成基础油和精选添加剂
- ▣ 优异的剪切稳定性提供稳定的动力.
- ▣ 适用于各种密封圈

典型物性:

测量项目	测量方法	
比重 @ 15 °C	ASTM D 4052	0.852
闪点 (开口杯), °C	ASTM D 92	198
倾点, °C	ASTM D 97	-45
运动粘度 @ 40°C (cSt)	ASTM D 445	32.2
@ 100°C (cSt)	ASTM D 445	7.2
粘度指数	ASTM D 2270	198
布氏粘度 @-40°C,mPas.s	ASTM D 2983	11260
外观	目测	绿色

Product Data Sheet



规格、认证及推荐:

AUDI / VW	TL 52180 G 052 180 G 052 516 A2	SFU	CHAIN
FORD	CFT30 WSS-M2C933-A MOTORCRAFT XT-7-QCFT MERC C	SFU	CHAIN
SUBARU	e-CVTF	SFU	CHAIN
BMW	83 22 0 136 376 83 22 0 429 154 EZL 799 EZL 799A	SFU	BELT
DAIHATSU	AMMIX CVTF-DTC	SFU	BELT
DODGE / JEEP	NS-2	SFU	BELT
FORD	CFT23	SFU	BELT
HONDA	CVTF 08200-9006 HMMF (without starting clutch)	SFU	BELT
MAZDA	CVTF 3320	SFU	BELT
MINI COOPER	83 22 0 136 376 EZL 799 EZL 799A ZF CVT V1	SFU	BELT
MITSUBISHI	DIAMOND QUEEN CVTF-J1	SFU	BELT
NISSAN	NS-1NS-2	SFU	BELT
PUNCH	EZL 799 EZL 799A	SFU	BELT
RENAULT	ELFMATIC	SFU	BELT
SATURN	22688912	SFU	BELT
SHELL	GREEN 1V	SFU	BELT
SUBARU	i-CVTF LINEARTRONIC CVTF K0425Y0710 CV-30	SFU	BELT
SUZUKI	CVT FLUID GREEN 1 CVT FLUID GREEN 2 VTF 3320	SFU	BELT
TOYOTA / LEXUS	TC	SFU	BELT