



UNITED UNIGEAR S5

9405G2GL5REV0

Product Description:

United Unigear S5 is a multi purpose gear lubricant manufactured from selected, highly refined base oil and blended with field-proven additives. This combination creates a product with excellent chemical and thermal stability over a wide range of temperature.

United Unigear S5 is designed to provide top-tier performance under extremely high pressure (EP Condition) by utilizing the core Sulfur-Phosphorus EP Technology. This advanced Chemistry allows the United Unigear S5 to be able to withstand the super high load between the teeth of those hypoid gear sets commonly found in modern vehicles' transmission system. United Unigear S5 having excellent thermal stability and corrosion resistance as well. It is blended with antifoam to suppress excess forming. The superior sulfur / phosphorus additives also are fully compatible with seals and gaskets.

Applications / Benefits:

- ▣ Proven gear protection in low and high-speed conditions.
- ▣ Reduces costs associated with seasonal oil changes.
- ▣ Improves fuel economy.
- ▣ Superior sulfur phosphorus additives.
- ▣ Easier low temperature starting.

Typical Characteristics:

Test Description	Method	90	140	80W-90	85W-90	85W-140
SAE Viscosity Grade	SAE J 300	90	140	80W-90	85W-90	85W-140
Specific Gravity @ 15 °C	ASTM D 4052	0.896	0.910	0.885	0.897	0.907
Flash Point, °C	ASTM D 92	208	215	210	212	215
Pour Point, °C	ASTM D 97	-9	-6	-27	-18	-12
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	198	402	139	172	389
cSt @ 100°C	ASTM D 445	17.1	27.8	14.7	16.5	27.4
Viscosity Index	ASTM D 2270	95	95	105	100	96
Color	ASTM D 1500	<3.0	<3.5	<2.5	2.5	3.0

Specifications, Approvals & Recommendations:

- API GL-5
- MIL L-2105D
- PRF-210SE

Product Data Sheet