

UNITED ATF

Product Description

Automatic Transmission Fluids formulated with new generation petroleum based products for automatic and powershift transmissions. The highest level product of ATF are suitable for use both GM Dexron III and Ford Mercon. In addition, it also meets Allison C-4 fluid and is qualified as a PSF specification.

These products provide superior wear protection for all passenger car and light trucks requiring the use of TASA, Dexron II D, Dexron II E or Dexron III G/H ATF.

Applications / Benefits

- * Provides excellent friction, oxidation and thermal stability
- * Outstanding anti-wear properties
- * Improves hydrolytic stability
- * Better cold temperature flow properties than SAE 10W motor oil

Typical Characteristics

Test Description	Method	Unit	TASA	DEXRON IID	DEXRON III G/H
Density @ 15 °C	ASTM D 4052	kg/L	0.856	0.854	0.853
Flash Point	ASTM D 92	°C	200	198	194
Pour Point	ASTM D 97	°C	-33	-36	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	40.2	37	35.7
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.7	7.4	7.3
Viscosity Index	ASTM D 2270	-	166	170	175
Appearance	Visual	-	Red	Red	Red

Specifications, Approvals & Recommendations

	TASA	DEXRON II D	DEXRON IIIG/H
* ALLISON	-	-	C4
* FORD	-	-	FORD M
* FORD	-	FORD ESP-M2C166-H	FORD ESP-M2C166-H
* FORD	-	FORD ESP-M2C138-CJ	FORD ESP-M2C138-CJ
* GM	-	-	D-IIIH
* GM	-	D-IIID	D-IIID
* GM	TASA	TASA	TASA
* MB	-	236.2	236.2

Reference No.
5391G2ATFREVO

Last revised date:
11/7/2023