

UNITED HYDRO VESTA VACUUM PUMP OIL

Product Description

Hydrotreated Industrial Oil formulated with highly refined Gp2 base stocks and specially selected additives designed to achieve premium performance that is suitable for mechanical vacuum pumps, particularly where good oil-water separation property, resistance to wear and oxidation, high viscosity index and long life service characteristics are required.

This product has a very narrow boiling spread and low volatility, as well as very low saturated steam pressure under high temperatures that guarantee high vacuum pressures are obtained.

Applications / Benefits

- * Very low saturated steam pressure
- * High viscosity index
- * Resistance to wear
- * Outstanding long-term oxidation stability

Typical Characteristics

Test Description	Method	Unit	ISO 68	ISO 100
ISO Viscosity Grade	-	-	ISO 68	ISO 100
Density @ 15 °C	ASTM D 4052	kg/L	0.886	0.885
Flash Point	ASTM D 92	°C	228	230
Pour Point	ASTM D 97	°C	-9	-9
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	68.2	98.1
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	8.7	11.0
Viscosity Index	ASTM D 2270	-	98	97

Reference No.
6521G2VACOILREV0

Last revised date:
7/12/2023