

UNITED CVTF NS-3

Product Description

Continuously Variable Transmission Fluid blended from high-performance fully synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

This oil is an automatic transmission well-balanced fluid specially designed for use in latest generations of Continuously Variable Transmissions (CVT) which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance of CVTs as compared with the regular automatic transmissions, many car makers have been adopting CVTs in more and more models.

Applications / Benefits

- * Excellent low temperature fluidity, reducing start up wear
- * Provides excellent friction, oxidation and thermal stability
- * Outstanding anti-wear properties and oil film thickness
- * Compatible with a wide range of seals

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.8385
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.18
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.201
Viscosity Index	ASTM D 2270	-	201
Appearance	Visual	-	Green

Specifications, Approvals & Recommendations

* AUDI/ VW	P/N G 052 180 (-A2)
* AUDI/ VW	P/N G 052 516 A2
* BMW/ MINI/ PUNCH	EZL 799
* BMW/ MINI/ PUNCH	EZL 799A
* BMW	P/N 83 22 0 136 376
* BMW	P/N 83 22 0 429 154
* CHERY	CVTF WCF-1
* CHRYSLER / FCA	MOPAR CVTF+4 P/N 05191184A
* DAIHATSU	AMMIX CVTF- DFE
* DAIHATSU	AMMIX CVTF- DTC
* DODGE/ JEEP	NS-2
* FCA	CVTF+4 P/N 05191184AA
* FORD	CFT23
* FORD	CFT30
* FORD	MERC C
* FORD	WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
* GM	CVTF I-GREEN2
* GM	CVT P/N 19260800
* GM	DEX-CVT
* GM	HP-CVT P/N19355873
* HONDA	CVTF P/N 08200-9006
* HONDA	HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
* HONDA	HCF-2 P/N 08200-HCF2
* HYUNDAI / KIA	SP-CVT 1
* IDEMITSU	CVTF-EX1
* MAZDA	CVTF 3320
* MINI COOPER	ZF CVT V1
* MITSUBISHI	DIAMOND GREEN CVTF-J1
* MITSUBISHI	DIAMOND GREEN CVTF-J4
* NISSAN	NS-1
* NISSAN	NS-2
* NISSAN	NS-3
* PROTON	PUNCH CVT; CVTF EX-1 (SFU)
* RENAULT	ELFMATIC
* SATURN	P/N 22688912
* SHELL	GREEN 1V
* SUBARU	LINEARTRONIC CVTF
* SUBARU	LINEARTRONIC CVTF-II; P/N K0425Y0711
* SUBARU	LINEARTRONIC CV-30 P/N K0425Y0710
* SUBARU	e-CVTF
* SUBARU	i-CVTF
* SUBARU	HIGH TORQUE P/N K0421Y0700

Specifications, Approvals & Recommendations

* SUZUKI	CVT FLUID GREEN 1
* SUZUKI	CVT FLUID GREEN 2
* SUZUKI	CVTF 3320
* SUZUKI	NS-2
* TOYOTA / LEXUS	FE
* TOYOTA / LEXUS	TC

Reference No.
5800G3LONS3REV3

Last revised date:
19-05-25