

UNITED M1 CLASSIC 4T

Product Description

Fully synthetic motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It is formulated using high quality synthetic oil and fortified with superior additives package. This product is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance.

This product is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits

- * Reduces engine wear and extends engine life
- * Protects engine under severe operating conditions
- * Retards harmful deposit formation on vital engine parts
- * Protects against rust and corrosion

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.849
Flash Point	ASTM D 92	°C	228
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	91.54
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.44
Viscosity Index	ASTM D 2270	-	164
TBN	ASTM D 2896	mgKOH/g	7
CCS	ASTM D 5293	cP	≤7000

Specifications, Approvals & Recommendations

- * API SP
- * JASO MA2

Reference No.
61209545G3SPMA2REV0

Last revised date:
25/10/2023