

UNITED MX SUPER 4T

Product Description

Hydrotreated motorcycle oil is a multigrade lubricant designed for four-stroke motorcycle engines. It contains a balanced blend of select high performance, high viscosity index base stocks and a special proprietary additive package. This motorcycle oil is engineered to provide unsurpassed wear protection, engine cleanliness and oxidation resistance, as well as consistent viscosity.

This is a powerful detergent type of motor oil. It can be used in most 4T engines including Yamaha, Honda, Kawasaki, Suzuki, and Kubota.

Applications / Benefits

- * Reduces engine wear and extends engine life
- * Protects engine under severe operating conditions
- * Retards harmful deposit formation on vital engine parts
- * Protects against rust and corrosion

Typical Characteristics

Test Description	Method	Unit				
SAE Viscosity Grade	SAE J 300	-	10W30	10W40	15W40	20W50
Density @ 15 °C	ASTM D 4052	kg/L	0.865	0.865	0.867	0.878
Flash Point	ASTM D 92	°C	216	218	220	248
Pour Point	ASTM D 97	°C	-30	-30	-27	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	76.65	100.9	112.9	183.2
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.79	14.83	14.69	20.01
Viscosity Index	ASTM D 2270	-	148	153	134	127
TBN	ASTM D 2896	mgKOH/g	6.0	6.0	6.0	6.0

Specifications, Approvals & Recommendations

- * API SL
- * JASO MA2

Reference No.
6128G2SLMA24TREV2

Last revised date:
09/07/2024