According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 1: IDENTIFICATION

1.1 GHS Product identifier: UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

Distillates (petroleum), hydrotreated heavy paraffinic, < 3 % IP 346, > 20,5 cSt @

40°C

CAS: 64742-54-7

Other means of identification:

Not relevant

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses (Consumer use): Lubricant Relevant uses (Professional users): Lubricant Relevant uses (Industrial user): Lubricant

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Manufacturer's or supplier's details:

UNITED OIL COMPANY PTE LTD 14 Tuas Drive 2, Singapore 638647 638647 Singapore - Singapore - Singapore Phone: +65 6861 1157 - Fax: +65 6861 3101 enquiry@united-oil.com

http://www.united-oil.com/default.aspx?uc=14 **Emergency phone number:** +65 68611157

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

SS 586: Part 2: 2022:

Classification of this product has been carried out in accordance with SS 586: Part 2: 2022

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

2.2 GHS label elements, including precautionary statements:

SS 586: Part 2: 2022:

Warning



Hazard statements:

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P261: Avoid breathing vapours

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality.

2.3 Other hazards which do not result in classification:

Not relevant

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Chemical description: Mixture based on hydrocarbons and additives In accordance with SS 586: Part3: 2022 (2023), the product contains:

Date of compilation: 15/4/2025 Version: 1 Page 1/10

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification	Concentration
CAS: 64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic , < 3 % IP 346, > 20,5 cSt @ 40°C	
CAS: 68955-53-3	Amines, C12-14-tert-alkyl Acute Tox. 2: H330; Acute Tox. 3: H311; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Flam. Liq. 4: H227; Skin Corr. 1B: H314; Skin Sens. 1A: H317 - Danger	<1 %
CAS: Not relevant	Alkyl methacrylate Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	<1 %
CAS: 112-90-3	(Z)-octadec-9-enylamine Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1: H304; Skin Corr. 1B: H314; STOT RE 2: H373; STOT SE 3: H335 - Danger	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

3.2 Mixtures:

Not relevant

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary first-aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation,however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not relevant

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective actions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Date of compilation: 15/4/2025 Version: 1 Page 2/10

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 5: FIRE-FIGHTING MEASURES (continued)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and materials for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 60 Months

Date of compilation: 15/4/2025 Version: 1 Page 3/10

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 7: HANDLING AND STORAGE (continued)

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters/Occupational exposure limits:

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

8.2 Appropriate engineering control measures:

A.- Individual protection measures, such as personal protective equipment (PPE)

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using chemical protection gloves

D.- Eye and face protection

Pictogram	PPE	Remarks
	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
Mandatory face protection		

E.- Bodily protection

Pictogram	PPE	Remarks		
	Work clothing	Replace before any evidence of deterioration.		
	Anti-slip work shoes	Replace before any evidence of deterioration.		

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	- ∰	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid

Appearance: Not relevant * Color: Not relevant * Odor: Not relevant * Odour threshold: Not relevant *

Volatility:

Boiling point at atmospheric pressure: Not relevant * Vapour pressure at 20 °C: Not relevant * Vapour pressure at 50 °C: Not relevant * Not relevant * Evaporation rate at 20 °C:

Product description:

Density at 20 °C: 888 kg/m³ Relative density at 20 °C: 0.89

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant *

Kinematic viscosity at 40 °C: ~157 mm²/s Kinematic viscosity at 100 °C: $\sim 15.5 \text{ mm}^2/\text{s}$ Concentration: Not relevant * pH: Not relevant *

Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Not relevant * Solubility properties: Not relevant * Decomposition temperature: Melting point/freezing point: Not relevant *

Flammability:

>200 °C Flash Point: Flammability (solid, gas): Not relevant * Autoignition temperature: Not relevant * Lower flammability limit: Not relevant * Upper flammability limit: Not relevant *

Particle characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 15/4/2025 Version: 1 Page 5/10

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Median equivalent diameter: Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

Not relevant *

components:

Other safety characteristics:

Surface tension at 20 °C:

Not relevant *

Refraction index:

Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and	friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not appli	cable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Not relevant

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Distillates (petroleum), hydrotreated heavy paraffinic , < 3 % IP 346, > 20,5 cSt @ 40°C	LD50 oral	>5000 mg/kg	
CAS: 64742-54-7	LD50 dermal	>5000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Amines, C12-14-tert-alkyl	LD50 oral	612 mg/kg	Rat
CAS: 68955-53-3	LD50 dermal	251 mg/kg	Rat
	LC50 inhalation vapour	0.5 mg/L	
Alkyl methacrylate	LD50 oral	>5000 mg/kg	
CAS: Not relevant	LD50 dermal	>5000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
(Z)-octadec-9-enylamine	LD50 oral	888 mg/kg	Rat
CAS: 112-90-3	LD50 dermal	>5000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 12: ECOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Amines, C12-14-tert-alkyl	LC50	1.3 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 68955-53-3	EC50	4.1 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	0.44 mg/L (72 h)	Selenastrum capricornutum	Algae
Alkyl methacrylate	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: Not relevant	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
(Z)-octadec-9-enylamine	LC50	>0.01 - 0.1 mg/L (96 h)		Fish
CAS: 112-90-3	EC50	>0.01 - 0.1 mg/L (48 h)		Crustacean
	EC50	>0.01 - 0.1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
Amines, C12-14-tert-alkyl	NOEC	0.078 mg/L	Oncorhynchus mykiss	Fish
CAS: 68955-53-3	NOEC	Not relevant		
(Z)-octadec-9-enylamine	NOEC	>0.01 - 0.1 mg/L		Fish
CAS: 112-90-3	NOEC	>0.01 - 0.1 mg/L		Crustacean

12.2 Persistence and degradability:

Not relevant

12.3 Bioaccumulative potential:

Not relevant

12.4 Mobility in soil:

Not relevant

12.5 Results of PBT and vPvB assessment:

Not relevant

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

Environmental Public Health (Toxic Industrial Waste) Regulations.

Hazardous Waste (Control of Export, Import and Transit) Act.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to SS 586-1 (2014):

Date of compilation: 15/4/2025 Version: 1

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: Not relevant
 14.2 UN proper shipping name: Not relevant
 14.3 Transport hazard class(es): Not relevant
 Labels: Not relevant
 14.4 Packing group, if applicable: Not relevant

14.5 Environmental hazard: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according Not relevant to Annex II of MARPOL 73/78 and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

14.1 UN number: Not relevant
 14.2 UN proper shipping name: Not relevant
 14.3 Transport hazard class(es): Not relevant
 Labels: Not relevant
 14.4 Packing group, if applicable: Not relevant

14.5 Marine pollutant: No

14.6 Special precautions for user

Special regulations: Not relevant

EmS Codes:

Physico-Chemical properties: see section 9
Limited quantities: Not relevant
Segregation group: Not relevant

14.7 Transport in bulk according
Not relevant

to Annex II of MARPOL 73/78 and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:

14.1 UN number: Not relevant
 14.2 UN proper shipping name: Not relevant
 14.3 Transport hazard class(es): Not relevant
 Labels: Not relevant
 14.4 Packing group, if applicable: Not relevant
 14.5 Environmental hazard: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

14.7 Transport in bulk according Not relevant to Annex II of MARPOL

73/78 and the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

Environmental Protection and Management (Hazardous Substances) Regulations.

Environmental Protection and Management Act. (EPMA) (CHAPTER 94A)

Environmental Public Health Act. (EPHA) (CHAPTER 95)

Fire Safety Act. (CHAPTER 109A)

Date of compilation: 15/4/2025 Version: 1

According to SS 586: Part3: 2022 (2023)



UNITED LSD UNIGEAR S5 SAE 80W90 API GL-5

SECTION 15: REGULATORY INFORMATION (continued)

Workplace Safety and Health Act. (CHAPTER 354A)

Workplace Safety and Health (General Provisions) Regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with SS 586: Part 3: 2022 (2023) - Specification for hazard communication for hazardous chemicals and dangerous goods - Part 3: Preparation of safety data sheets (SDS).

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

SS 586: Part 2: 2022:

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H311 - Toxic in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 4: H227 - Combustible liquid.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://www.nea.gov.sg

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.