

UNITED ATF MV 88

Product Description

Fully synthetic automatic transmission fluid formulated with selected high viscosity index synthetic base stocks and latest additive technology that provides excellent service in a wide variety of North American, European, and Asian vehicles.

This product is recommended for use in all GM vehicles DII, DIII(G), DIII(H). It exceeds the published JASO 1A or Allison C-4 fluid specifications and meets the requirements of Toyota Type T-IV level of anti-shudder durability (ASD).

Applications / Benefits

- * Provides excellent oxidation and thermal stability for longer life
- * Superior wear protection to protect critical transmission components
- * Excellent viscosity stability (high VI), application in a wide variety of Auto Transmissions
- * Enhanced fluidity at very low temperature service

Typical Characteristics

Test Description	Method	Unit	
Density @ 15 °C	ASTM D 4052	kg/L	0.853
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	35.38
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	6.86
Viscosity Index	ASTM D 2270	-	157
Appearance	Visual	-	Red/ Amber



United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



Specifications, Approvals & Recommendations

* AISIN	JWS 3309 ATF, ATF-0T4
* ALLISON	389
* ALLISON	C2
* ALLISON	C3
* ALLISON	C4
* ATF	3100 PL085
* ATF	3403-M115
* ATF	ETL-7045 E
* ATF	K17
* ATF	LA 2634
* ATF	N402
* ATF	SP-III
* BMW	ATF4
* BMW	ETL-7045
* BMW	ETL-7045 E
* BMW	ETL-8072B
* BMW	LA 2634
* BMW	LT 71141
* BMW	P/N 81 22 9 400 272
* BMW	P/N 81 22 9 400 275
* BMW	P/N 81 22 9 407 858
* BMW	P/N 81 22 9 407 859
* BMW	P/N 83 22 0 024 249
* BMW	P/N 83 22 0 024 359
* BMW	P/N 83 22 0 026 922
* BMW	P/N 83 22 0 402 413
* BMW	P/N 83 22 0 403 248
* BMW	P/N 83 22 0 403 249
* BMW	P/N 83 22 2 220 438
* BMW	P/N 83 22 2 220 440
* BMW	P/N 83 22 2 220 442
* BMW	P/N 83 22 7 542 290
* BMW	P/N 83 22 9 407 765
* BMW	P/N 83 22 9 407 807
* BOSCH	BOSCH TE-ML 09
* CITROEN	Z 000169756
* DAIHATSU	D3-SP
* FCA	ASRC
* FCA	ATF+
* FCA	ATF+2
* FCA	ATF+3
* FCA	ATF+4



United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



Specifications, Approvals & Recommendations

* FCA	FIAT 9.55550-AV1
* FCA	FIAT 9.55550-AV4
* FCA	MB 236.10, P/N 05127382AA
* FCA	MB 236.12, P/N 05127382AA
* FCA	P/N 68333587AA
* FCA	SP-III
* FCA	TYPE 7176E
* FCA	TYPE 9602
* FORD	ESP-M2C138-CJ
* FORD	ESP-M2C166-H
* FORD	P/N XT-2-QDX [M]
* FORD	P/N XT-2-QSM [SYN]
* FORD	P/N XT-5-QM [V]
* FORD	P/N XT-5-QSM [V SYN]
* FORD	P/N XT-8-QAW [PREMIUM]
* FORD	P/N XT-9- QMM5 [FNR5]
* FORD	SPEC WSS-M2C922-A1
* GM	ATF Z1, SATURN P/N 22717466
* GM	DEX [GM 6032M]
* GM	DEX-B [GM 6032M]
* GM	DEX-IIC [6137M]
* GM	DEX-IID [GM 6137M]
* GM	DEX-IIE [GM 6137M]
* GM	DEX-IIIF [GM 6297M]
* GM	DEX-IIIG [GM 6417M]
* GM	DEX-IIIH [GM N10055]
* GM	P/N 19 40 700
* GM	P/N 19 40 767
* GM	P/N 21005966
* GM	P/N 88900925
* GM	P/N 9985010
* GM	P/N 9986195
* GM	SATURN T-IV FLUID, SATURN P/N 22689186
* GM	TYPE A SUFFIX A
* HONDA/ACURA	ATF Z1, P/N 08200-9001
* HONDA/ACURA	ATF Z1, P/N 08200-9001A
* HYUNDAI/KIA	ATF RED-1K
* HYUNDAI/KIA	GENUINE ATF
* HYUNDAI/KIA	JWS 3314
* HYUNDAI/KIA	P/N 00232-19023
* HYUNDAI/KIA	P/N 04500-00140
* HYUNDAI/KIA	P/N UM040 CH20 RED-1



United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



Specifications, Approvals & Recommendations

* HYUNDAI/KIA	SP
* HYUNDAI/KIA	SP-II
* HYUNDAI/KIA	SP-III
* ISUZU	ATF II
* ISUZU	ATF III
* ISUZU	GENUINE ATF
* ISUZU	P/N 08200-9001
* JAGUAR	JLM 20238
* JAGUAR	JLM 20292
* JAGUAR	JLM 21044
* JAGUAR	K17, JATCO 3100 PL085
* JAGUAR	LT 71141
* JAGUAR	WSS-M2C922-A1
* JAMA	JASO M315, CLASS 1-A
* LAND ROVER	ATF N402
* LAND ROVER	JWS3309US
* MAN	339A
* MAN	339D
* MAN	339F
* MAZDA	ATF M-5 P/N 0000-23-ATF -M5
* MAZDA	ATF N-1
* MAZDA	ATF S-1
* MAZDA	F-1
* MAZDA	JWS3317
* MAZDA	M3
* MAZDA	TYPE T-IV, JWS 3309 ATF
* MERCEDES	A 0019892203
* MERCEDES	ATF 3403-M115
* MERCEDES	SHEET 236.1
* MERCEDES	SHEET 236.10
* MERCEDES	SHEET 236.11
* MERCEDES	SHEET 236.2
* MERCEDES	SHEET 236.5
* MERCEDES	SHEET 236.8
* MINI	ATF JWS 3309, P/N 83 22 0 402 413
* MITSUBISHI	ATF-J2
* MITSUBISHI	DIA QUEEN AW
* MITSUBISHI	DII
* MITSUBISHI	DIII
* MITSUBISHI	SP, P/N MS991156
* MITSUBISHI	SP-II
* MITSUBISHI	SP-III



United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



Specifications, Approvals & Recommendations

* NISSAN	FLUID A
* NISSAN	MATIC D
* NISSAN	MATIC J, P/N 999MP-MTJ00P
* NISSAN	MATIC K
* NISSAN	N402
* PEUGEOT	P/N Z 000169756
* PORSCHE	JWS 3309, P/N 000 043 205 28
* PORSCHE	LT 71141
* PORSCHE	P/N 000 043 204 41
* PORSCHE	P/N 000 043 204 63
* PORSCHE	P/N 000 043 305 42
* PORSCHE	P/N 958 300 901 00
* PORSCHE	P/N 999 917 547 00 (A2) or P/N 000 043 205 09
* PSA	AL4, P/N 9730AE
* PSA	4HP20, P/N 9730AE
* PSA	B71 2340
* RENAULT	DP-0
* RENAULT	MATIC D2
* RENAULT	SATF-D
* ROLLS ROYCE	OIL NO. PL 31493PA
* SAAB	ATF HP
* SAAB	JWS 3309
* SAAB	P/N 93 160 393
* SATURN	DEX-IIIG
* SATURN	T-IV FLUID, P/N 22689186
* SSANGYONG	DSIH 5M-52
* SSANGYONG	DSIH 5M-66
* SUBARU	ATF HP, P/N K0140Y0700, P/N SOA635040
* SUZUKI	ATF 2326
* SUZUKI	ATF 2384K
* SUZUKI	ATF 3314
* SUZUKI	ATF 3317
* SUZUKI	ATF 5D06
* SUZUKI	MATIC D
* SUZUKI	MATIC J
* TOYOTA	JWS 3309, TYPE T-IV, P/N 08886-81015
* TOYOTA	TYPE D-II
* TOYOTA	TYPE T
* TOYOTA	TYPE T-II
* TOYOTA	TYPE T-III
* VOLVO	P/N 1161521
* VOLVO	P/N 1161621



United Oil
PERFORMANCE • VALUE • RELIABILITY

A member of the Repsol Group



Specifications, Approvals & Recommendations

* VOLVO	P/N 1161640; P/N 1161540
* VOLVO CE	97340, AT100
* VOLVO CE	97341, AT101
* VW/AUDI	G 052 162 (-A1, -A2) [AG4]
* VW/AUDI	G 052 990 A2
* VW/AUDI	G 055 025 (-A2)
* VW/AUDI	G US 000 162
* VW/AUDI	LT 71141
* ZF	LIFEGUARDFLUID 5 (ZF No. S671 090 170)
* ZF	TE-ML 05L
* ZF	TE-ML 11A
* ZF	TE-ML 11B
* ZF	TE-ML 21L

Reference No.
5392G3ATFREVI

Last revised date:
18-10-24