

UNITED M5 HYPER 4T

Product Description

Fully Synthetic 4T Motorcycle Oil delivering the latest development in lubricating oil technology. This premium formulation is reinforced with a top-tier additive developed for motorcycle engines and Polyalphaolefins (PAO) for excellent thermal/oxidative stability and extended engine life. Meeting API SP standards, it is ideal for high-performance motorcycles and demanding conditions.

This product exceeds the requirements of emission control and oil consumption, ensuring optimal engine performance. The combination of wear protection and enhanced lubrication reliability ensures engine durability and long-term cost-effectiveness.

Applications / Benefits

- * Silk smooth operation for high performance engines
- * High temperature deposit control
- * Optimal catalyst durability and fuel economy
- * Wear protection and extended service life

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8583
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	125
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	18.8
Viscosity Index	ASTM D 2270	-	170
TBN	ASTM D 2896	mgKOH/g	6.8

Specifications, Approvals & Recommendations

- * API SP
- * JASO MA2

Reference No.
6120G34SPMA2M5HYPREV0

Last revised date:
13-03-25