

UNITED M5 SONIC 4T

Product Description

Fully Synthetic motorcycle oil formulated with the latest advancements in lubricating technology, this product provides optimal protection for modern engines. Enhanced with a robust additive package and contains Polyalphaolefins (PAO).

It meets the highest API SP performance standards and surpasses stringent requirements for emissions control and oil consumption management in contemporary engines.

Applications / Benefits

- * Super fluidity over a wide temperature range and operating conditions
- * Forms a strong emulsion to protect the oil pumping system
- * Minimizes harmful effects of lubricant contamination
- * Good control of wear and sludge formation

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	10W50
Density @ 15 °C	ASTM D 4052	kg/L	0.8583
Flash Point	ASTM D 92	°C	230
Pour Point	ASTM D 97	°C	-36
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	125
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	18.8
Viscosity Index	ASTM D 2270	-	170
TBN	ASTM D 2896	mgKOH/g	6.8

Suggested for the following Uses

- | | |
|--------|-----|
| * API | SP |
| * JASO | MA2 |