

UNITED XTG-Q

Product Description

Gasoline engine oil formulated with selected base fluids and technologically advanced additive to deliver outstanding engine performance and protection for today's gasoline engine powered cars and trucks. It meets the performance requirement of API SQ specification with enhanced properties in the areas of piston cleanliness, wear protection, fuel efficiency and prolong engine life.

Applications / Benefits

- * Silky smooth operation for all high-performance engines.
- * Increases emission system durability and improves fuel efficiency.
- * Improves piston cleanliness and sludge control.
- * Excellent anti-wear properties and extends service life.

Typical Characteristics

Test Description	Method	Unit	10W30	10W40	15W40	20W50
SAE Viscosity Grade	SAE J 300	-	10W30	10W40	15W40	20W50
Density @ 15 °C	ASTM D 4052	kg/L	0.8680	0.8681	0.8710	0.8784
Flash Point	ASTM D 92	°C	218	220	224	242
Pour Point	ASTM D 97	°C	-30	-30	-27	-18
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	73.77	101.2	108.4	172
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	11.12	14.81	14.6	19.49
Viscosity Index	ASTM D 2270	-	141	153	139	130
TBN	ASTM D 2896	mgKOH/g	7.2	7.2	7.2	7.2

Specifications, Approvals & Recommendations

* API	SQ-RC IN SAE 10W30
* API	SQ IN SAE 15W40 & 20W50
* ILSAC	GF-7A IN SAE 10W30

Suggested for the Following Uses

* API	SQ IN SAE 10W40
-------	-----------------

Reference No.
51574166G2SQREV0

Last revised date:
09-04-25